

Lap Sealant HS

1. Description

Firestone Lap Sealant is designed to seal and mechanically protect the exposed cut edge of QuickSeam Products. Lap Sealant is also used as a general purpose sealant in other applications as specified by current Firestone specifications and details.

2. Preparation

Surfaces on which Lap Sealant is to be applied must be clean, dry, and free from loose and foreign materials, oil and grease. The surfaces that are to be sealed must be cleaned with QuickPrime Plus. Wait minimum 4 hours between splicing and application of Lap Sealant. Under bad weather conditions, Lap Sealant must be applied before the end of the working day. Restore to room temperature prior to use, if exposed to lower temperatures (< 15°C) for a prolonged period.

3. Application

The sealant is applied with a mastic gun at the specified location using the plastic nozzle applicator supplied by Firestone, being sure to keep the nozzle applicator centred over the lap step-off. Take care to leave a mound of Lap Sealant directly over the splice edge.

4. Coverage

Coverage rate of 6 to 7 lm per tube.

5. Characteristics

Technical	■ Base	EPDM
	■ Colour	Black
	■ Solvents	Light aliphatic solvent
	■ Solids (%)	Min. 80
	■ Specific gravity	1.34 - 1.46
	■ Flash point (°C)	11

6. Packaging / Storage / Shelf Life

Packaging: 25 tubes/carton.

Storage: Dry and clean. Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf Life: 12 months, when stored in above-mentioned conditions. Shelf life will be reduced if exposed to higher temperatures.

7. Precautions

Flammable. Keep away from sources of ignition. Do not smoke when using. For professional use only. Use only in well ventilated areas. Avoid contact with skin and eyes. Refer to Material Safety Data Sheets. Keep out of the reach of children. Recommended cleaner is rubbing alcohol followed by soap and water.

