

# ACCU SYNC™

Gain unparalleled pressure regulation for any Hunter valve.

## OPERATING SPECIFICATIONS

- Regulation from 1.4 to 7.0 bar; 140 to 700 kPa
- Static pressure: 10 bar; 1,000 kPa
- Required dynamic pressure differential: 1.0 bar; 100 kPa
- Works with AC- and DC-latching solenoids
- Works with any Hunter valve
- Warranty period: 2 years

ACCU SYNC VALVE RECOMMENDED FLOW RANGE		
Valve	Flow	
	m³/hr	l/min
PGV-100/101	1.2–6.8	19–114
PGV-151	4.5–28	75–454
PGV-201	9.0–34	150–750
ICV-101	1.2–9.0	19–150
ICV-151	4.5–31	75–510
ICV-201	9.0–34	150–560
ICV-301	34–68	565–1135
IBV-101	1.2–9.0	19–150
IBV-151	4.5–31	75–510
IBV-201	9.0–46	150–560
IBV-301	34–68	565–1135

ACCU SYNC APPLICATIONS		
● Adjustable 1.4 to 7.0 bar	For full customisation, the adjustable Accu Sync can regulate pressure from 1.4 to 7.0 bar; 140 to 700 kPa	
● Fixed 2.1 bar	Ideal for spray systems, pressure-regulated to 2.1 bar; 210 kPa	
● Fixed 2.8 bar	Ideal for MP Rotator nozzles and large in-line drip systems, pressure-regulated to 2.8 bar; 280 kPa	

## ADJUSTABLE



AS-ADJ  
Height with solenoid: 8 cm

## ADAPTER



SOLENOID ADAPTER

## FIXED



AS-30  
Height with solenoid: 8 cm



AS-40  
Height with solenoid: 8 cm



## Installation

Accu Sync shown installed on ICV and PGV valves.